

## Chapter 6: User-Defined Functions I

### Extra Programming Examples

### Laboratory Exercises (1)

---

1. An Example that uses the **cmath header file** and the **floor function**.

```
#include <iostream>
#include <cmath>
using namespace std;

int main()
{
    double x = 55.99, y;
    y = floor(x);
    cout<<y<<endl;
    return 0;
}
```

Note: Try other cmath functions such as ceil, pow, exp, etc

---

2. An Example that uses the **cstdlib header file** and the **abs function**.

```
#include <iostream>
#include <cstdlib>
using namespace std;

int main()
{
    int x = -13, y;
    y = abs(x);
    cout<<y<<endl;
    return 0;
}
```

---

3. An Example that uses the **cctype header file** and the **abs function**.

```
#include <iostream>
#include <cctype>
using namespace std;

int main()
{
    int a;
```

```
a = islower('A');
cout<<a<<endl;
return 0;
}
```

---

#### 4. The command return a, b;

```
#include <iostream>
using namespace std;

int return_function_example()
{
    int x = 5;
    int y = 9;
    return x,y;
}

int main()
{
    cout<<"the out of the above function is";
    cout<<return_function_example()<<endl;
    return 0;
}
```

Note: try **return y, x;** and see the difference.

---

#### 5. An example of a value-returning function: **courseGrade**

```
#include <iostream>
using namespace std;
char courseGrade(int score)
{
    switch(score/10)
    {
        case 0:
        case 1:
        case 2:
        case 3:
        case 4:
        case 5: return 'F';
        case 6: return 'D';
        case 7: return 'C';
        case 8: return 'B';
        case 9:
```

```

        case 10: return 'A';
    default: return 'X';
}
}

int main()
{
    int grade;
    char x;
    cout<<"Enter a grade"<<endl;
    cin>>grade;
    x = courseGrade(grade);
    cout<<x<<endl;
    return 0;
}

```

---

6. An example of a value-returning function: courseGrade using nested if and string header file.

```

#include <iostream>
#include<string>
using namespace std;

string courseGrade(int score)
{
    if (score <=100 and score >=95)
        return "A+";
    else if (score <95 and score >=90)
        return "A";
    else if (score <90 and score >=85)
        return "B+";
    else if (score <85 and score >=80)
        return "B";
    else if (score <80 and score >=75)
        return "C+";
    else if (score <75 and score >=70)
        return "C";
    else if (score <70 and score >=65)
        return "D+";
    else if (score <65 and score >=60)
        return "D";
    else if (score <60 and score >=0)
        return "F";
    else return "Error";
}

```

```
int main()
{
    int grade;
    string x;
    cout<<"Enter grade"<<endl;
    cin>>grade;
    x = courseGrade(grade);
    cout<<x<<endl;
    return 0;
}
```

---

7. Write a C++ program that uses the function **larger** to determine the largest number from a set of 5 numbers

```
#include <iostream>
using namespace std;

double larger(double x, double y)
{
    if(x >= y)
        return x;
    else
        return y;
}

int main()
{
    int num, max;
    cout<<"Enter 5 numbers"<<endl;
    cin>>num;
    max = num;

    for(int i = 0; i < 4; i++)
    {
        cin>>num;
        max = larger(max, num);
    }

    cout<<"The larger number is: "<<max<<endl;
    return 0;
}
```

---